

Reciprocating Thermostatic Shaking Water Bath

Features:

- * Power off recovery function.
- * Audio and visual alarm.
- * Stainless steel lid, prevent heat loss and evaporation.
- * Double over-temperature protection design. Anti dry-out function.



Technical Parameters:

Model	SCHWLR45	SCHWLR80	SCHWLR160
Control	PID		
Display	LCD		
Shaking Mode	Reciprocating shaking		
Drive Mode	Balancing drive		
Shaking Speed	20~200rpm		
Shaking Accuracy	±1rpm		
Vibration Range	Φ25mm		
Standard Capacity	Universal spring clamp	250ml*24	250ml*48
Max. Capacity	250ml*12 or 500ml*8 or 1000ml*6	250ml*24 or 500ml*15 or 1000ml*8	250ml*48 or 500ml*30 or 1000ml*20
Shaking Plate Size	430*320mm	590*390mm	780*586mm
Spring Shaking Plate Size	430*320*60mm	590*390*80mm	780*586*80mm
Timing Range	0~999.59h		
Temp. Range	RT~100℃		
Temp. Accuracy	±0.1℃		
Temp. Uniformity	±0.2℃		
Internal Material	316 stainless steel		
Safety Function	Audio and visual alarm for over-temperature; Alarm for over-speed; Detached over-temperature protector; Shutdown protection for door opening; Leakage or overcurrent protection		
Consumption	2000W	2200W	4000W
Power Supply	AC110/220V±10%, 50/60Hz		
Internal Size(W*D*H) mm	510*380*240	700*455*260	940*660*275
External Size(W*D*H) mm	760*420*370	945*495*408	1240*700*760
Package Size(W*D*H) mm	810*470*470	995*545*508	1740*750*860
Gross Weight(kg)	65	120	160