



## Apparatuur voor uw laboratorium

De scherpste prijs voor de beste kwaliteit



SY-1L4H



SY-1L1H



SY-2L8H

### Features:

- \* Stainless steel inner chamber and upper cover.
- \* Adopt new design structure, which could avoid the leakage of steam.
- \* PID microprocessor controller, LED display.
- \* With universal fixture for SY-1L4H and SY-1L6H.

### Technical Parameters:

Model	SY-1L1H	SY-1L2H	SY-1L4H	SY-1L6H	SY-2L4H	SY-2L6H	SY-2L8H
Capacity	3L	7L	13L	20L	15L	23L	24L
Temp. Range	RT.-100°C						
Temp. Fluctuation	±0.5°C						
Temp. Accuracy	±1°C						
Time Range	0-999min						
Power	300W	500W	1000W	1500W	1000W	1500W	2000W
Power Supply	AC110/220V±10%, 50/60Hz						
Internal Size(mm)	140*150*150	300*150*150	600*180*120	900*180*120	320*300*150	500*300*150	620*320*120
External Size(mm)	270*180*190	320*180*210	770*310*170	1100*310*170	340*320*210	500*320*210	750*360*160
Packing Size(mm)	320*230*220	410*220*310	820*330*250	1150*330*250	410*390*310	590*390*310	830*460*250
Net Weight(kg)	2	4	10	13	6.5	9	12
Gross Weight(kg)	3	5	11	14.5	7.5	10	13